



120-277V,
50/60Hz



PRODUCT OVERVIEW

ETI's Sellado Vapor Tight Series is designed with a robust polycarbonate housing and durable stainless-steel latches to prevent moisture and dirt from compromising the housing and damaging internal wiring and components. Vapor Tights are weatherproof and rated IP65 to protect against dust and hose-down applications. With **3 Color Preference®** field-selectable CCT and **3 Lumen Boost®** selectable wattage, this series is ideal for a variety of applications such as car washes, food processing plants, and more.

Integrated LED with diffused lens

Long Life: > 175,000 hours (L70)

3 CCT: 3500K, 4000K, 5000K | CRI: 80+


-4°F to 104°F (-20°C to 40°C)

Battery Back Up, Occupancy Sensor and Cord with Plug Options Available

Model #	Description	Energy/Performance		Dimensions/Weights			
		Watts (3 selectable)	Lumens	L	W	H	weight (lbs)
64507101	2' Vapor Tight	20/25/30W	2600-3900	23.6"	5.0"	3.7"	3.64
64508101	4' Vapor Tight	25/35/50W	3250-6500	47.2"	5.0"	3.7"	5.95
64509101	8' Vapor Tight	60/75/90W	7800-11700	94.5"	5.0"	3.9"	13.45




Easy access to CCT & Wattage Select switch underneath lens



Series	Size	Power	CRI	CCT	Voltage	Dim.	Sensors	BBU	Cords
SLVT	2 (2')	LB3	8	CP3	MV	LVD	OS	EM	CC6NTL120V
Sellado	4 (4')	(Lumen Boost)	80+ CRI	3 CCT	120-277V	0-10V Dimming	OC Sensor (Blank) No Sensor	8W Emergency Battery Backup (Blank) No BBU	6', 14/3 So Cord w/NEMA Twist Lock - 120V Plug
Vapor Tight Series	8 (8')								CC6NTL277V 6', 14/3 So Cord w/NEMA Twist Lock - 277V Plug (Blank) No Cord

OPTIONS



Suspension and surface mounting kits included

3 Color Preference® **3 LUMEN BOOST®**

